



**SPECIFICATION**

Size	DN 15 -50
Material	Body SS316L Head SS316L
Temperature	Cold 0-50c / Hot 0-130c
Pressure	16 Bar
Power Supply	—
Output	Pulse (Option)
Protection Grade	IP 68
Connection	Screw
Accuracy	+/- 2%
Measurement Range	—
Repeatability	—
Explosion Proof	—
ISO 9001 & ISO 4064	
Warranty 2 Years ( Full Service & Spare Parts)	
4 Variant Available : Cold / Cold Pulse / Hot / Hot Pulse	
Pulse DN 15 - 50 : 1/10 L	

**APPLICATION**

Water, Sea Water, Corrosive, Chemical, Food Grade



**TECHNICAL DATA**

SIZE		FLOW RANGE (m3/h)				DIMENSION (mm)			WEIGHT (kg)
DN (mm)	INCH	MINIMUM FLOW	TRANSITIONAL FLOW	CONTINUOUS FLOW	MAXIMUM FLOW	L (mm)	B (mm)	H (mm)	
DN 15	1/2"	0.03	0.12	1.5	3	165	98	116	1.5
DN 20	3/4"	0.05	0.2	2.5	5	190	98	117	1.7
DN 25	1"	0.07	0.28	3.5	7	260	103.5	124	2.4
DN 32	1 1/4"	0.12	0.48	6	12	260	103.5	124	2.7
DN 40	1 1/2"	0.2	0.8	10	20	300	125	162	4.5
DN 50	2"	0.45	3	15	30	300	125	162	7.2