



SPECIFICATION

Size	DN 10 - 200
Material	Head Epoxy Coated Aluminium Body Epoxy Coated Cast Iron Flange Epoxy Coated Cast Iron
Temperature	Cold 0-100c / Hot 0-(120/200c)(Opt)
Pressure	16 Bar
Power Supply	—
Output	—
Protection Grade	IP 68
Connection	PN 16
Accuracy	+/- 0.5%
Measurement Range	—
Repeatability	—
Explosion Proof	—
OHSAS 18001:2007 - ISO 9001:2008 - ISO 14001:2004 Warranty 2 Years (Full Service & Spare Parts)	
Counter Reading Litre Resettable & Totalizer	

APPLICATION

Oil, Light Palm Oil, Diesel Fuel, Kerosene



TECHNICAL DATA

DN (mm)	SIZE INCH	FLOW RANGE (m ³ /h)		DIMENSION (mm)				WEIGHT (kg)	
		3-200 cPs	200-2000 cPs	L	B	H		COLD	HOT
						COLD	HOT		
DN 10	3/8"	0.1-0.6	0.04-0.2	150	100	209	—	6	—
DN 15	1/2"	0.25-1.5	0.15-1	170	118	226	—	8	—
DN 20	3/4"	0.5-3	0.3-1.5	200	150	238	—	11	—
DN 25	1"	1-6	0.6-3	260	180	246	406	18	—
DN 40	1 1/2"	2.5-15	1.5-10	245	180	271	445	20	—
DN 50	2"	4-24	2.4-15	340	250	379	700	46	—
DN 65	2 1/2"	6-40	4-20	420	325	443	—	87	—
DN 80	3"	8-50	5-26	420	325	443	760	87	—
DN 100	4"	16-100	10-50	515	418	467	785	160	—
DN 150	6"	32-190	19-100	540	515	565	865	245	—
DN 200	8"	54-340	34-190	650	650	624	925	400	—