



SPECIFICATION

Size	DN 15 - 150
Material	Head Epoxy Coated Aluminium Body Epoxy Coated Aluminium Flange Epoxy Coated Aluminium
Temperature	Cold 0-60c / Hot 0-(120/180/240c)(Opt)
Pressure	16 Bar
Power Supply	—
Output	Pulse (Opt)
Protection Grade	IP 68
Connection	PN 16
Accuracy	+/- 0.5%
Measurement Range	—
Repeatability	—
Explosion Proof	—
OHSAS 18001:2007 - ISO 9001:2008 - ISO 14001:2004 Warranty 2 Years (Full Service & Spare Parts)	
Counter Reading Litre Resettable & Totalizer	

APPLICATION

Oil, Light Palm Oil, Diesel Fuel, Kerosene, Gasoline



TECHNICAL DATA

SIZE		FLOW RANGE (m3/h)		DIMENSION (mm)				WEIGHT (kg)	
DN (mm)	INCH	3-150 cPs	L	B	H		COLD	HOT	
					COLD	HOT			
DN 15	1/2"	0.4-3	160	95	227	—	6	—	
DN 20	3/4"	—	—	—	—	—	—	—	
DN 25	1"	1-6	180	110	297	427	8	12	
DN 40	1 1/2"	2.5-16	240	178	338	—	21	30	
DN 50	2"	4-25	265	178	362	492	26	41	
DN 65	2 1/2"	6-50	265	252	341	—	40	52	
DN 80	3"	10-60	265	252	341	471	40	52	
DN 100	4"	16-100	350	310	423	—	86	110	
DN 150	6"	32-200	550	455	550	680	202	215	