



SPECIFICATION

Size	DN 15 - 40
Material	Body Brass Head ABS
Temperature	0-50c
Pressure	16 Bar / 25 Bar (Opt)
Power Supply	Battery 3.6V
Output	Pulse / 4-20 mA / RS 485
Protection Grade	IP 68
Connection	Screw
Accuracy	—
Measurement Range	—
Repeatability	—
Explosion Proof	—
ISO 4064, GBT 778.1-2007, JJG 162-2009	
Warranty 2 Years (Full Service & Spare Parts)	
Power Consumption < 2.7 AH/ year	

APPLICATION

Water, Filtered Water, Sea Water, Sewage



TECHNICAL DATA

SIZE		CONNECTION	PRESSURE (Mpa)	FLOW RANGE (m3/h)		DIMENSION (mm)			WEIGHT (kg)
DN (mm)	INCH			MIN FLOW	MAX FLOW	L	B	H	
DN 15	1/2"	SCREW	1.6	0.0125	3.125	110	148	185.5	2.3
DN 20	3/4"	SCREW	1.6	0.016	4	130	148	197	2.5
DN 25	1"	SCREW	1.6	0.020	5	160	148	200	2.8
DN 40	1 1/2"	SCREW	1.6	0.032	7.875	180	148	208	3.3