



## SPECIFICATION

Size	DN 15 - 25
Material	Body Epoxy Coated Cast Iron Flange Epoxy Coated Cast Iron Mesh Filter SS304
Temperature	0-150c
Pressure	16 Bar
Power Supply	—
Output	—
Protection Grade	IP 68
Connection	Flange PN 16
Accuracy	—
Measurement Range	—
Repeatability	—
Explosion Proof	—
ISO 9001 & ISO 4064	
Warranty 2 Years ( Full Service & Spare Parts)	

## APPLICATION

Filter for separating dirt from oil.



## TECHNICAL DATA

SIZE		FLANGE	PRESSURE (Bar)	MESH SIZE (mm)	HOLE - SIZE (pc - mm)	DIMENSION (mm)			WEIGHT (kg)
DN (mm)	INCH					L	B	H	
DN 10	3/8"	PN 16	16	3.9	4-14	150	90	125	1.8
DN 15	1/2"	PN 16	16	3.9	4-14	150	95	125	3.95
DN 20	3/4"	PN 16	16	20	4-14	180	105	153	2.7
DN 25	1"	PN 16	16	20	4-14	180	115	153	—
DN 40	1 1/2"	PN 16	16	20	4-18	300	150	304	—
DN 50	2"	PN 16	16	20	4-18	300	165	304	—
DN 80	3"	PN 16	16	1.6	8-18	400	200	420	—
DN 100	4"	PN 16	16	1.6	8-18	500	220	502	—
DN 150	6"	PN 16	16	1.6	8-23	600	285	650	—
DN 200	8"	PN 16	16	1.6	12-23	786	340	770	—