

Main Features

OGM-A-25/40/50 aluminum oval gear meter has the ability to handle a wide range of fluid viscosities with exceptional levels of repeatability and durability, applying in the petroleum, chemical, food industry, etc.



MODEL	SIZE	MIN FLOW RATE	MAX FLOW RATE	ACCURACY	REPEATABILITY	MAX VISCOSITY	MAX OPERATING PRESSURE
OGM-A-25	1"	20 l/min	120 l/min	±0.5%	≤ 0.03%	1000CPS	3.4MPa
OGM-A-40	1 1/2"	25 l/min	250 l/min	±0.5%	≤ 0.03%	1000CPS	1.8MPa
OGM-A-50	2"	30 l/min	300 l/min	±0.5%	≤ 0.03%	1000CPS	1.8MPa

Main Features

Cast Iron oval gear meter has the ability to handle a wide range of fluid viscosities with exceptional levels of repeatability and durability, applying in the petroleum, chemical, food industry, etc.



MODEL	SIZE	MIN FLOW RATE	MAX FLOW RATE	ACCURACY	REPEATABILITY	MAX OPERATING PRESSURE	MAX OPERATING TEMPERATURE
LC - A10	3/8"	0.8//min	8//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A15	1/2"	2//min	25//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A20	3/4"	5//min	50//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A25	1"	10//min	100//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A40	1 - 1/2"	25//min	250//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A50	2"	60//min	300//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A80	3"	140//min	700//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A100	4"	160//min	1600//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A150	6"	300//min	3000//min	±0.5%	≤ 0.03%	18 BAR	100 °C
LC - A200	8"	500//min	5000//min	±0.5%	≤ 0.03%	18 BAR	100 °C

This documents and its contents are proprietary and confidential and may not be disclosed without express permission in writing.