

615B

DC 1500V
AC 1000V



Technical data

Model	615B	
Basic Function	Range	Accuracy
DC Voltage	600mV/6V/60V	±(0.5%+7)
	600V/1500V	±(1.0%+10)
AC Voltage	6V/60V	±(1.0%+10)
	600V/1000V	±(1.0%+12)
Low impedance	6V/60V	±(1.0%+10)
AC voltage	300V	±(1.0%+12)
DC current	60A/600A/1000A	±(4.0%+10)
AC current	60A/600A/1000A	±(4.0%+10)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ	±(1.0%+5)
	20MΩ	±(1.5%+15)
	60MΩ	±(2.5%+20)
Capacitance	1nF	±(5.0%+40)
	10nF/100nF/1uF/10uF/100uF/1mF/10mF	±(5.0%+10)
Frequency	10Hz~10MHz	±(0.3%+3)
Duty cycle	10.0%~90.0%	±(0.3%+3)
Temperature	(-20~1000)°C/(-4~1832)°F(Standard 250°Cprobe)	±(2.0%+5)

General functions

Display mode	LCD	Display mode	√
Max display	5999	Max display	√
Diode/on-off	√	Diode/on-off	(0~40)°C <75%RH
NCV	√	NCV	(-10~50)°C <80%RH
Data retention	√	Data retention	Highest display OL
Backlit display	√	Backlit display	40~1kHz
Low voltage	√	Low voltage	φ40mm
Line of fire judgment	√	Line of fire judgment	φ39mm
Flashlight lighting	√	Flashlight lighting	10MΩ
Automatic shutdown	√	Automatic shutdown	Two AAA batteries
V.F.C	√	V.F.C	230*75*40mm
Surge current	√	Surge current	About 313g

6015F



Basic Function	Range	Accuracy
DC Voltage	2V/20V/200V/1000V	±(2.0%+5)
AC Voltage	200V/750V	± (1.2%+5)
AC Current	20A/200A/1000A	± (2.0%+5)
Resistance	200Ω/2KΩ/20KΩ/200KΩ/2MΩ	± (1.0%+2)
Frequency	2kHz/20kHz	±(3.0%+15)
Diode Test	√	
Continuity Buzzer	√	
Low Battery Indication	√	
Data Hold	√	
Input Impedance	10MΩ	
Sampling Rate	3 times/s	
AC Frequency Response	(50-60)Hz	
Operation Way	Auto range	
Max. Display	1999	
Clamp Size	55mm	
Battery	9V(6FF2)	
Product Net Weight	Approx: 270g	
Standard Accessories	Test leads, battery, instruction manual	
Standard Inner Packing	Color box	
Standard Quantity Per Carton	30pcs	

6266



Technical data

Basic Function	Range	6266
DC voltage	1000V	±(0.8%+2)
AC voltage	750V	±(1.2%+4)
AC Current	200A/1000A	±(3.0%+5)
Resistance	200 Ω/20k Ω	±(1.0%+1)

Product color	Case: black
Product net weight	Approx: 310g
Standard accessories	Test leads, battery, instruction manual, TP01 temperature probe
Standard inner packing	Color box
Standard Quantity Per Carton	30pcs/ctn
Carton size	465×317×506mm
Standard Gross Weight	Approx: 16.8kg

Special Function	6266
Continuity buzzer	√
Low battery buzzer	√
Hold	Data hold
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	(50~60)Hz
Operation way	Manual range
Max. Display	1999
Clamp size	50mm
Power	9V(6FF2)

Technical data

Basic skills	Range	Precision
DC voltage	200mV/2V/20V/200V	±(0.5%+7)
	600V	±(1.0%+20)
AC voltage	2V/20V/200V	±(0.8%+10)
	600V	±(1.2%+25)
DC current	200uA/2000uA/20mA	±(1.2%+3)
	200mA	±(1.5%+3)
AC current	200uA/2000uA/20mA	±(1.8%+3)
	200mA	±(2.0%+3)
	2A	±(4.0%+50)
	20A	±(4.0%+35)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ	±(1.0%+5)
	20MΩ	±(1.5%+15)

New Model



3218+

3218A

Special Function	3218+	3218A
Continuity buzzer	√	
Diode test	√	
Low battery indication	√	√
Hold	Peak value hold	Data hold
Auto power off	√	√
Lamp	√	√
Function protection	√	√
Input impedance	10MΩ	10MΩ
Sampling rate	3 times/s	3 times/s
AC Frequency response	50Hz~60Hz	50Hz~60Hz
Operation way	Manual range/Auto range	Manual range
Max. Display	1999	1999
Clamp size	30mm	30mm
Power	3V(1.5V×2)	3V(1.5V×2)

3 1/2

